

Water Jet Machine



Main Features

- * Effective removal of plasters from molds after casting.
- * WaterJet adjustable until a pressure of 120 bar.
- * Ecological technology: works without acids, solvents or other substances harmful to the environment.
- * Stainless steel booth with internal lighting.
- * Supplied as standard: washing pump at 120 bar, high pressure hose for connection to the washing booth and supporting trolley.



Idroget 120	
Power supply	220 V, 50 Hz
Pump power	2.2 hp
Pump pressure adjustable	120 bar
Pump delivery rate	8 ltr/min
External dimensions (L x D x H)	620 x 500 x 1400 mm

Vacuum Pump



Rotary vane is synonymous with a robust, functional construction. R5 rotary vane vacuum pumps are characterized by an optimum design and perfectly synchronized components and materials. The constantly high vacuum level in continuous operation is ensured by recirculating oil lubrication and state of the art precision manufacturing. A sophisticated oil separator ensures efficient use of oil.

	R5 RA 0025 F	R5 RA 0040 F
Nominal pump speed	25 m ³ /h	40 m ³ /h
Ultimate pressure	0.1 hPa (mbar)	0.1 hPa (mbar)
Nominal motor rating	1.0 kW	1.4 kW
Nominal motor speed	1500 min ⁻¹	1500 min ⁻¹
Power consumption at 100 mbar	0.8 kWh	1.1 kWh
Power consumption at ultimate pressure	0.5 kWh	0.6 kWh
Noise level (ISO 2151)	60 dB (A)	63 dB (A)
Oil capacity	1 l	1 l
Weight approx.	36 kg	42 kg
Dimensions (L x W x H)	585 x 284 x 263 mm	625 x 284 x 263 mm
Gas inlet / outlet	G 1 1/4" / G 1 1/4"	G 1 1/4" / G 1 1/4"



HAR Water Chiller

WC-150L



Specifications	
Trade name	HAR Water Chiller
Model	WC-150L
Tank Capacity	150 liter
Pump	0.5 hp, 2 motors Motor from Pedrollo(Italy)
Electricity	15 amp, 220V/Single phase
AC Unit	2 ton
Compressor type	Gas compressor
Refrigerant gas	R-22

